

1.394 GHz External Transmitter

160mW



1.394GHz External Transmitter 160mW

Video and Audio Transmission

Technical Data

Transmission power	160 mW
Frequency range	1,394 GHz
Range indoors	Depending on the gain factor of the antenna the range can be improved up to 14 times compared to the standard range
Range outdoors	Depending on the gain factor of the antenna the range can be improved up to 14 times compared to the standard range
Video input	Composite colour picture signal pos. 1 +/- 0,1Vpp
Video bandwidth	30 Hz - 7 MHz
Modulation mode	F3F (Video/(<i>*Audio</i> if applicable) frequency modulated)
AV switching channel	- <i>**10</i> kOhm
Switching channel frequency	- / <i>*Ton A</i> 32 kHz
Frequency control input	- / <i>*10</i> kOhm
Power supply	12 V
Current demand	160mA
Weight	370 g
Protection class	IP 54
Ambient temperatures (use/store)	-10 - +55°C / -20 - +60°C
Air humidity	max. 70% non-condensing

Connectors

Trigger/Switching channel input	- <i>*Cinch</i> / <i>*RCA</i>
Video input	- <i>*Cinch</i> / <i>*RCA</i>
Dimensions	180x120x70
12 V DC	DC (2,5/5,5 mm)